



## DESIGN REPORT OF SAFETY DATA SHEET

No.: 230100320453628E

Date: Aug.30,2023



<b>Name of the sample</b>	Rechargeable Li-ion Battery UP2500		
<b>Applicant</b>	Pylon Technologies Co., Ltd.		
<b>Supplier</b>	Pylon Technologies Co., Ltd.		
<b>Composition of the sample</b>	Lithium Iron Phosphate(LFP): 40.5%; Aluminum: 6%; Graphite: 25%; Copper: 8.5%; Electrolyte(EMC/EC/PC/LiPF6): 20%		
<b>Warranty of Design</b>	GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS (GHS) Ninth revised edition		
Design Result of SDS please see next page.			
<b>Designer</b>		<b>Approver</b>	For and on behalf of <b>CCIC JIANGSU CO., LTD.</b> 中国检验认证集团江苏有限公司 

4

授权签字人 Authorized Signature (s)

Notes: This SDS is valid before the implementation of the Tenth revised edition GHS.



Rechargeable Li-ion Battery UP2500

## SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

SDS

Date: Aug.30,2023

### Section 1 Product and Company Identification

#### > Product Identifier

Product Name	Rechargeable Li-ion Battery UP2500
Synonyms	-
CAS No.	Not applicable
EC No.	Not applicable
Molecular Formula	Not applicable

#### > Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Relevant Identified Uses	Please consult manufacturer.
Uses Advised Against	Please consult manufacturer.

#### > Details of the Supplier of the Safety Data Sheet

Applicant Name	Pylon Technologies Co., Ltd.
Application Address	No.73, Lane 887, Zu Chongzhi Road, Zhangjiang Hi-Tech Park Pudong, Shanghai 201203, China
Applicant Post Code	201203
Applicant Telephone	+86-21-51317697
Applicant Fax	+86-21-51317698
Applicant E-mail	li.lanqiang@pylontech.com.cn
Supplier Name	Pylon Technologies Co., Ltd.
Supplier Address	Plant 8, No.505 Kunkai Road, JinXi Town, Kunshan City, Jiangsu Province, PEOPLE'S REPUBLIC OF CHINA
Supplier Post Code	201203
Supplier Telephone	+86-21-51317697
Supplier Fax	+86-21-51317697
Supplier E-mail	Liu.chaojin@pylontech.com.cn

#### > Emergency Phone Number

Emergency Phone Number	+86-21-51317697
------------------------	-----------------

### Section 2 Hazards Identification

Hazard class and label elements of the product according to GHS (the ninth revised edition):

#### > GHS Hazard Class





Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

SDS

Date: Aug.30,2023

This product meets the definition of an article. Under the Globally Harmonized System of Classification and Labeling of Chemicals (GHS), "Articles" as defined in the Hazard Communication Standard (29 CFR 1910.1200) of the Occupational Safety and Health Administration of the United States of America, or by similar definition, are outside the scope of the system. [Rev.9 (2021) Part 1.3.2.1.1]

## > GHS Label Elements

**Pictogram** Not applicable

**Signal Word** **Not applicable**

## > Hazard Statements

Not applicable

## > Precautionary Statements

### Prevention

Do not open or disassemble.  
Do not expose to high temperatures or open fire.  
Do not mix with batteries of varying sizes, chemistries or types.  
Avoid using external impact battery.

### Response

Not applicable

### Storage

Store under roof in cool, dry, well-ventilated areas.

### Disposal

Dispose of contents/container in accordance with local/regional/national/ international regulations.

## Section 3 Composition/Information on Ingredients

Component	CAS No.	EC No.	Concentration (weight percent, %)
Lithium Iron Phosphate(LFP)	15365-14-7	-	40.5
Aluminum	7429-90-5	231-072-3	6
Graphite	7782-42-5	231-955-3	25
Copper	7440-50-8	231-159-6	8.5
Electrolyte(EMC/EC/PC/Li PF6)	-	-	20



Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

SDS

Date: Aug.30,2023

## Section 4 First Aid Measures

### > Description of First Aid Measures

**General Advice**

Immediate medical attention is required. Show this safety data sheet (SDS) to the doctor in attendance.

**Eye Contact**

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.

**Skin Contact**

Take off contaminated clothing and shoes immediately. Wash off with plenty of water for at least 15 minutes and consult a physician if feel uncomfortable.

**Ingestion**

Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

**Inhalation**

Move victim into fresh air. If breathing is difficult, give oxygen. Do not use mouth to mouth resuscitation if victim ingested or inhaled the substance. If not breathing, give artificial respiration and consult a physician immediately.

**Protecting of First-aiders**

Ensure that medical personnel are aware of the substance involved. Take precautions to protect themselves and prevent spread of contamination.

### > Most Important Symptoms and Effects, both Acute and Delayed

- 1 Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

### > Indication of Any Immediate Medical Attention and Special Treatment Needed

- 1 Treat symptomatically.
- 2 Symptoms may be delayed.

## Section 5 Fire Fighting Measures

### > Extinguishing Media

**Suitable Extinguishing Media**

Dry chemical, carbon dioxide or alcohol-resistant foam.

**Unsuitable Extinguishing Media**

Do not use a solid water stream as it may scatter or spread fire.

### > Specific Hazards Arising from the Substance or Mixture

- 1 Containers may explode when heated.
- 2 Fire exposed containers may vent contents through pressure relief valves.
- 3 May expansion or decompose explosively when heated or involved in fire.

### > Advice for Firefighters

- 1 As in any fire, wear self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) and full protective gear.
- 2 Fight fire from a safe distance, with adequate cover.
- 3 Prevent fire extinguishing water from contaminating surface water or the ground water system.





Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

SDS

Date: Aug.30,2023

## Section 6 Accidental Release Measure

### > Personal Precautions, Protective Equipment and Emergency Procedures

- 1 Ensure adequate ventilation. Remove all sources of ignition.
- 2 Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
- 3 Use personal protective equipment. Avoid breathing vapours, mist, gas or dust.

### > Environmental Precautions

- 1 Prevent further leakage or spillage if safe to do so.
- 2 Discharge into the environment must be avoided.

### > Methods and Materials for Containment and Cleaning Up

- 1 Absorb spilled material in dry sand or inert absorbent. In case of large amount of spillage, contain a spill by bunding.
- 2 Adhered or collected material should be promptly disposed of, in accordance with appropriate laws and regulations.
- 3 Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

## Section 7 Handling and Storage

### > Precautions for Handling

- 1 Handling is performed in a well ventilated place.
- 2 Wear suitable protective equipment.
- 3 Avoid contact with skin and eyes.
- 4 Keep away from heat/sparks/open flames/ hot surfaces.
- 5 Take precautionary measures against static discharges.

### > Precautions for Storage

- 1 Keep containers tightly closed.
- 2 Keep containers in a dry, cool and well-ventilated place.
- 3 Keep away from heat/sparks/open flames/ hot surfaces.
- 4 Store away from incompatible materials and foodstuff containers.

## Section 8 Exposure Controls/Personal Protection

### > Control Parameters

#### Occupational Exposure Limit Values

Component	Country/Region	Limit Value - Eight Hours	Limit Value - Short Term
-----------	----------------	---------------------------	--------------------------



Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

## SDS

Date: Aug.30,2023

		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Aluminum 7429-90-5	USA - OSHA	-	15	-	-
	South Korea	-	10	-	-
	Ireland	-	1	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	5	-	10
	Australia	-	10	-	-
Graphite 7782-42-5	USA - OSHA	-	15	-	-
	South Korea	-	2	-	-
	Ireland	-	10	-	-
	Germany (DFG)	-	4	-	-
	Denmark	-	2.5	-	5
	Australia	-	3 (4)	-	-
Copper 7440-50-8	The Netherlands	-	0.1	-	-
	Poland	-	0.2	-	-
	Latvia	-	0.5	-	1
	Germany (DFG)	-	0.01	-	0.02

### Biological Limit Values

No information available

### Monitoring Methods

- 1 EN 14042 Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.
- 2 GBZ/T 160 Determination of toxic substances in workplace air(Series effective standard)and GBZ/T 300 Determination of toxic substances in workplace air(Series standard).

### > Engineering Controls

- 1 Ensure adequate ventilation, especially in confined areas.
- 2 Ensure that eyewash stations and safety showers are close to the workstation location.
- 3 Use explosion-proof electrical/ventilating/lighting/equipment.
- 4 Set up emergency exit and necessary risk-elimination area.

### > Personal Protection Equipment

<b>Eye Protection</b>	Tightly fitting safety goggles (approved by EN 166(EU) or NIOSH (US).
<b>Hand Protection</b>	Wear protective gloves (such as butyl rubber) , passing the tests according to EN 374(EU),US F739 or AS/NZS 2161.1 standard. If exposure limits are exceeded or if irritation or other symptoms are experienced, use a full-face respirator with multi-purpose combination (US) or type AXBEK (EN 14387) respirator cartridges.
<b>Respiratory protection</b>	
<b>Skin and Body Protection</b>	Wear fire/flame resistant/retardant clothing and antistatic boots.





Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

SDS

Date: Aug.30,2023

## Section 9 Physical and Chemical Properties

<b>Appearance:</b> Lithium-ion batteries, individually packaged. Battery parameters: 25.6V 111Ah 2.8416kWh	<b>Odor:</b> No information available
<b>Odor Threshold:</b> No information available	<b>pH:</b> No information available
<b>Melting Point/Freezing Point (°C):</b> No information available	<b>Initial Boiling Point and Boiling Range (°C):</b> No information available
<b>Flash Point (°C)( Closed Cup):</b> Not applicable	<b>Evaporation Rate:</b> Not applicable
<b>Flammability:</b> No information available	<b>Upper/lower explosive limits[%(v/v)]:</b> Upper limit: No information available; Lower limit: No information available
<b>Vapor Pressure (KPa):</b> Not applicable	<b>Relative Vapour Density(Air=1):</b> Not applicable
<b>Relative Density(Water=1):</b> No information available	<b>Solubility:</b> No information available
<b>n-Octanol/Water Partition Coefficient:</b> No information available	<b>Auto-Ignition Temperature(°C):</b> No information available
<b>Decomposition Temperature (°C):</b> No information available	<b>Kinematic Viscosity (mm<sup>2</sup>/s):</b> Not applicable
<b>Particle characteristics:</b> No information available	<b>Critical Temperature(°C):</b> Not applicable

## Section 10 Stability and Reactivity

<b>Reactivity</b>	Contact with incompatible substances can cause decomposition or other chemical reactions.
<b>Chemical Stability</b>	Stable under proper operation and storage conditions.
<b>Possibility of Hazardous Reactions</b>	Ultrafine powder will self-ignite in the air at room temperature. Mixtures with metallic acetylene, when heated, cause a fire or incandescence. Reacts severely with halogens, interhalogens or other strong oxidants, or causes a fire.
<b>Conditions to Avoid</b>	Incompatible materials, heat, flame and spark.
<b>Incompatible Materials</b>	Oxidants, halogen, interhalogen and mercury. Metal acetylide, halogen, interhalogen, halogen oxides, nitric acid, nitrous oxide, nitrates, nitrites, halogen oxyacid salts, chromates, permanganates, inorganic peroxides, metal oxides and peroxyformic acid. Halogen, interhalogen, strong oxidant, water and acids.
<b>Hazardous Decomposition products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11 Toxicological Information

### > Acute Toxicity



Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

## SDS

Date: Aug.30,2023

Component	CAS No.	LD <sub>50</sub> (Oral)	LD <sub>50</sub> (Dermal)	LC <sub>50</sub> (Inhalation, 4h)
Aluminum	7429-90-5	50-300mg/kg(Rat)	275mg/kg(Rat)	No information available

### > Skin Corrosion/Irritation

No information available

### > Serious Eye Damage/Irritation

No information available

### > Skin Sensitization

No information available

### > Respiratory Sensitization

No information available

### > Germ Cell Mutagenicity

No information available

### > Carcinogenicity

ID	CAS No.	Component	IARC	NTP
1	15365-14-7	Lithium Iron Phosphate(LFP)	Not Listed	Not Listed
2	7429-90-5	Aluminum	Not Listed	Not Listed
3	7782-42-5	Graphite	Not Listed	Not Listed
4	7440-50-8	Copper	Not Listed	Not Listed
5	-	Electrolyte(EMC/EC/PC/LiPF6)	Not Listed	Not Listed

### > Reproductive Toxicity

No information available

### > Reproductive Toxicity (Additional)

No information available

### > STOT-Single Exposure

No information available

### > STOT-Repeated Exposure





Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

Warranty of Design: GHS (Ninth Revised Edition)

SDS

No.: 230100320453628E

Date: Aug.30,2023

No information available

## > Aspiration Hazard

No information available

## Section 12 Ecological Information

### > Acute Aquatic Toxicity

Component	CAS No.	Fish	Crustaceans	Algae
Aluminum	7429-90-5	LC <sub>50</sub> : 1.55mg/L (96h)(Fish)	No information available	No information available
Copper	7440-50-8	LC <sub>50</sub> : 0.665mg/L (96h)(Fish)	EC <sub>50</sub> : 0.02mg/L (48h)	ErC <sub>50</sub> : 7.9mg/L (96h)

### > Chronic Aquatic Toxicity

No information available

### > Others

**Persistence and Degradability**  
**Bioaccumulative Potential**  
**Mobility in Soil**

No information available

No information available

No information available

**Results of PBT and vPvB Assessment**

Lithium Iron Phosphate(LFP) does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Aluminum does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Graphite does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

Copper does not meet the criteria for PBT and vPvB according to Regulation (EC) No 1907/2006, annex XIII.

## Section 13 Disposal Considerations

**Waste Chemicals Contaminated Packaging Disposal Recommendations**

Before disposal should refer to the relevant national and local laws and regulation. Containers may still present chemical hazard when empty. Keep away from hot and ignition source of fire. Return to supplier for recycling if possible. Refer to Waste chemicals and Contaminated packaging.



Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

Warranty of Design: GHS (Ninth Revised Edition)

SDS

No.: 230100320453628E

Date: Aug.30,2023

## Section 14 Transport Information

Transporting Label



Marine pollutant

No

UN Number

3480

UN Proper Shipping Name

LITHIUM ION BATTERIES(including lithium ion polymer batteries)

Transport Hazard Class

9

Transport Subsidiary Hazard Class

NONE

Packing Group

Packagings shall conform to the packing group II performance level

Report remarks

According to United Nations Recommendations on the Transports of Dangerous Goods•Model Regulations, Lithium batteries(group) could be transported in accordance with the classification conclusions of this report when meet the requirements of UN38.3 test.

## Section 15 Regulatory Information

### > International Chemical Inventory

Component	EINECS	TSCA	DSL	IECSC	NZIoC	PICCS	KECI	AICS	ENCS
Lithium Iron Phosphate(LFP)	√	√	√	×	×	×	√	×	×
Aluminum	√	√	√	√	√	√	√	√	×
Graphite	√	√	√	√	√	√	√	√	×
Copper	√	√	√	√	√	√	√	√	×
Electrolyte(EMC/EC/PC/LiPF6)	×	×	×	×	×	×	×	×	×

【EINECS】 European Inventory of Existing Commercial Chemical Substances.

【TSCA】 United States Toxic Substances Control Act Inventory.

【DSL】 Canadian Domestic Substances List.

【IECSC】 China Inventory of Existing Chemical Substances.

【NZIoC】 New Zealand Inventory of Chemicals.

【PICCS】 Philippines Inventory of Chemicals and Chemical Substances.

【KECI】 Existing and Evaluated Chemical Substances.

【AICS】 Australia Inventory of Chemical Substances.

【ENCS】 Existing And New Chemical Substances.

Note





Rechargeable Li-ion Battery UP2500

# SAFETY DATA SHEET

Warranty of Design: GHS (Ninth Revised Edition)

SDS

No.: 230100320453628E

Date: Aug.30,2023

"√" Indicates that the substance included in the regulations  
"x" That no data or included in the regulations

## Section 16 Additional Information

Creation Date	Aug.30,2023
Revision Date	Aug.30,2023
Reason for Revision	-

### > Disclaimer

This Safety Data Sheet (SDS) was prepared according to UN GHS (the 9th revised edition). The data included was derived from international authoritative database and provided by the enterprise. Other information was based on the present state of our knowledge. We try to ensure the correctness of all information. However, due to the diversity of information sources and the limitations of our knowledge, this document is only for user's reference. Users should make their independent judgment of suitability of this information for their particular purposes. We do not assume responsibility for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product.



Rechargeable Li-ion Battery UP2500

**SAFETY DATA SHEET**

No.: 230100320453628E

Warranty of Design: GHS (Ninth Revised Edition)

**SDS**

Date: Aug.30,2023



**Terms of the Using of the Report**



1. The report is issued by CCIC according to the information of the chemicals and the information of its shipping provided by the applicant (shipper or his agent).
2. According to the demand of this SDS, CCIC requires the applicant to provide true and exact sample and data.
3. Information from applicant is the key of this SDS, so CCIC will not respond for the wrong of applicant.
4. Unless otherwise stated, the results shown in this test report refer only to the sample(s) tested.
5. This report will be effective only after it is signed by the inspector, approver and stamped by CCIC.
6. CCIC guarantees the objectivity and fairness of this report, and carries out confidentiality obligations on business secrets such as business information, technical documents and so on.
7. The partly duplicating of this report is prohibited without the written approver of CCIC.
8. The report is invalid when anything of the following happens-illegal transfer, embezzlement, imposture, modification or tampering in any media form.
9. The authenticity of the certificate can be checked by scan the security code of this certificate.